



End plate, Width: 2.7 mm, Colour: Black

RAL: 9005

Business data

| Dusiness data | |
|--|---------------|
| Article number | <u>2047.4</u> |
| Article name | AP SI BK |
| GTIN (EAN) | 4044211130183 |
| Packaging unit | 20 |
| Quantity unit | PC |
| Weight per piece (not including packaging) | 4.76 g |
| Weight per piece (including packaging) | 4.91 g |
| Unit of weight | G |
| Customs number | 85389099 |
| Country of origin | DE |
| Prio-Article | 2047.2 |
| Product description | End plate |



| Technical data | | |
|----------------------------------|---------------|--|
| Dimensions | | |
| Length | 53.8 mm | |
| Width | 2.7 mm | |
| Min. thickness | 2.7 mm | |
| Height | 41.6 mm | |
| Materials | | |
| Material | Polyamide 6.6 | |
| Flammability class UL 94 | V-2 | |
| Working temperature, min. | -40 °C | |
| Working temperature, max. | 105 °C | |
| Further technical data | | |
| Designed as end plate | ✓ | |
| Snap-on available | ✓ | |
| Environmental Product Compliance | | |
| REACH Candidate Substance Note | No | |



Media



Accessories

##INVERSE##CONTA-CONNECT



Fused terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 10 mm², Width: 12.2 mm, Colour: Black

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|--------------------------------|---------------|----------------|
| 1004.4 | SK 1/35 24V AC LED(RD) PA-G BK | 4044211129989 | 20 ST |



Fused terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 10 mm², Width: 12.2 mm, Colour: Black

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|--------------------------------|---------------|----------------|
| 1119.4 | SK 1/35 48V AC LED(RD) PA-G BK | 4044211130008 | 20 ST |



Fused terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 10 mm², Width: 12.2 mm, Colour: Black

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|---------------------------|---------------|----------------|
| <u>1375.4</u> | SK 1/35 230V AC G PA-G BK | 4044211129941 | 20 ST |



Fused terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 10 mm², Width: 12.2 mm, Colour: Black

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|--------------------------------|---------------|----------------|
| <u>1380.4</u> | SK 1/35 24V DC LED(RD) PA-G BK | 4044211129972 | 20 ST |



Fused terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 10 mm², Width: 12.2 mm, Colour: Black

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|-----------------|---------------|----------------|
| 1367.4 | SK 1/35 PA-G BK | 4044211128555 | 20 ST |



Fused terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 10 mm², Width: 12.2 mm, Colour: Black

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|--------------------------------|---------------|----------------|
| 1067.4 | SK 1/35 48V DC LED(RD) PA-G BK | 4044211129996 | 20 ST |



##INVERSE##CONTA-CONNECT



Fused terminal with screw cap for indicator fuses 5x25 mm, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 10 mm², Width: 12.2 mm, Colour: Black

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|----------------------|---------------|----------------|
| 1368.4 | SK 1/35 m.K. PA-G BK | 4044211129811 | 20 ST |



Fused terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 10 mm², Width: 12.2 mm, Colour: Black

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|---------------------------|---------------|----------------|
| 1376.4 | SK 1/35 115V AC G PA-G BK | 4044211129958 | 20 ST |