Data sheet 2141.0 AQI 10/6/11 YE





External insulated cross-connector, No. of poles: 10, Mounting type: Plug in, Width: 59.6 mm, Rated current: 27 A; Colour: Yellow

RAL: 1026

Business data

Article number	<u>2141.0</u>
Article name	AQI 10/6/11 YE
GTIN (EAN)	4044211049621
Packaging unit	10
Quantity unit	PC
Weight per piece (not including packaging)	5.95 g
Weight per piece (including packaging)	5.96 g
Unit of weight	G
Customs number	85389099
Country of origin	DE
Product description	External insulated cross-connector
Colour	Yellow

Data sheet





Dimensions Width 59.6 mm Fitch size 6 mm Ratings Rated current 27 A Contamination degree 3 Connection data No. of poles 10 Waterials Waterial Copper Surface Tin-plated Insulation housing Polyamide 6.6 Flammability class UL 94 Working temperature, min. 40 °C Working temperature, max. 105 °C Further technical data Wounting type Plug in Insulation available Verouch protection is available Verouch prote	Technical data		
Pitch size 6 mm Ratings Rated current 27 A Contamination degree 3 Connection data No. of poles 10 Materials Material Copper Surface Tin-plated Insulation housing Polyamide 6.6 Flammability class UL 94 V-2 Working temperature, min40 °C Working temperature, max. 105 °C Further technical data Mounting type Plug in Insulation available V Fouch protection is available V Fouch protection is available V Funder of bridged terminals 10 Environmental Product Compliance REACH Conform yes REACH Reference date 2023-06-14 REACH Candidate Substance Note	Dimensions		
Rated current 27 A Contamination degree 3 Connection data No. of poles 10 Materials Material Copper Surface Tin-plated Insulation housing Polyamide 6.6 Flammability class UL 94 Working temperature, min40 °C Working temperature, max. 105 °C Further technical data Mounting type Plug in Insulation available V Insulation	Width	59.6 mm	
Rated current 27 A Contamination degree 3 Connection data No. of poles 10 Materials Material Copper Surface Tin-plated Insulation housing Polyamide 6.6 Flammability class UL 94 Working temperature, min40 °C Working temperature, max. 105 °C Further technical data Mounting type Plug in Insulation available V Fouch protection is available V Fouch protection is available V Fumber of bridged terminals 10 Environmental Product Compliance REACH Conform yes REACH Reference date 2023-06-14 REACH Candidate Substance Note No	Pitch size	6 mm	
Rated current 27 A Contamination degree 3 Connection data No. of poles 10 Materials Material Copper Surface Tin-plated Insulation housing Polyamide 6.6 Flammability class UL 94 Working temperature, min40 °C Working temperature, max. 105 °C Further technical data Mounting type Plug in Insulation available V Fouch protection is available V Fouch protection is available V Fumber of bridged terminals 10 Environmental Product Compliance REACH Conform yes REACH Reference date 2023-06-14 REACH Candidate Substance Note No	Ratings		
Connection data No. of poles 10 Materials Material Copper Surface Tin-plated Insulation housing Polyamide 6.6 Flammability class UL 94 Morking temperature, min40 °C Morking temperature, max. 105 °C Further technical data Mounting type Plug in Insulation available V I	Rated current	27 A	
Materials Material Copper Surface Tin-plated Insulation housing Polyamide 6.6 Flammability class UL 94 Morking temperature, min. Mounting type Plug in Insulation available Fouch protection is available Number of bridged terminals REACH Conform MEACH Reference date REACH Candidate Substance Note Topper Topper Tin-plated Tin-plated Topper Topper Tin-plated Topper	Contamination degree	3	
Materials Material Copper Surface Tin-plated Insulation housing Polyamide 6.6 Flammability class UL 94 Morking temperature, min. Morking temperature, max. Mounting type Plug in Insulation available Fouch protection is available Mumber of bridged terminals Environmental Product Compliance REACH Conform REACH Reference date REACH Candidate Substance Note Tin-plated Touper Toup	Connection data		
Copper Surface Tin-plated Insulation housing Polyamide 6.6 Flammability class UL 94 Working temperature, min. Working temperature, max. 105 °C Further technical data Wounting type Plug in Insulation available Fouch protection is available Number of bridged terminals Environmental Product Compliance REACH Conform Yes REACH Reference date REACH Candidate Substance Note Tin-plated Ton-plated Polyamide 6.6 Following 6. Following 6. Following 6. Following 6. Following 6. Followi	No. of poles	10	
Surface Tin-plated nsulation housing Polyamide 6.6 Flammability class UL 94 Working temperature, min. Working temperature, max. 105 °C Further technical data Mounting type Plug in nsulation available Fouch protection is available Number of bridged terminals REACH Conform REACH Reference date REACH Candidate Substance Note Tin-plated Tin-plated Tin-plated Tin-plated Tin-plated Tolyamide 6.6 Polyamide 6.6 V-2 Value -40 °C -40	Materials		
Polyamide 6.6 Flammability class UL 94 Working temperature, min. Working temperature, max. 105 °C Further technical data Mounting type Plug in Insulation available Fouch protection is available Number of bridged terminals REACH Conform REACH Reference date REACH Candidate Substance Note Polyamide 6.6 V-2 V-2 Plug in Plug in 10 Plug in No	Material	Copper	
Flammability class UL 94 Working temperature, min. -40 °C Working temperature, max. 105 °C Further technical data Mounting type Plug in Insulation available Fouch protection is available V Number of bridged terminals Environmental Product Compliance REACH Conform yes REACH Reference date REACH Candidate Substance Note No	Surface	Tin-plated	
Working temperature, min. -40 °C Working temperature, max. 105 °C Further technical data Mounting type Plug in nsulation available Fouch protection is available Vumber of bridged terminals Environmental Product Compliance REACH Conform yes REACH Reference date REACH Candidate Substance Note No	Insulation housing	Polyamide 6.6	
Working temperature, max. Further technical data Mounting type Plug in Insulation available Fouch protection is available Number of bridged terminals 10 Environmental Product Compliance REACH Conform REACH Reference date 2023-06-14 REACH Candidate Substance Note No	Flammability class UL 94	V-2	
Further technical data Mounting type Plug in Insulation available Fouch protection is available Number of bridged terminals 10 Environmental Product Compliance REACH Conform yes REACH Reference date 2023-06-14 REACH Candidate Substance Note No	Working temperature, min.	-40 °C	
Mounting type Plug in Insulation available Fouch protection is available Number of bridged terminals 10 Environmental Product Compliance REACH Conform REACH Reference date 2023-06-14 REACH Candidate Substance Note No	Working temperature, max.	105 °C	
nsulation available Fouch protection is available Number of bridged terminals Environmental Product Compliance REACH Conform yes REACH Reference date REACH Candidate Substance Note No	Further technical data		
Fouch protection is available Number of bridged terminals Environmental Product Compliance REACH Conform REACH Reference date REACH Candidate Substance Note No	Mounting type	Plug in	
Number of bridged terminals 10 Environmental Product Compliance REACH Conform yes REACH Reference date 2023-06-14 REACH Candidate Substance Note No	Insulation available	✓	
Environmental Product Compliance REACH Conform yes REACH Reference date 2023-06-14 REACH Candidate Substance Note No	Touch protection is available	✓	
REACH Conform yes REACH Reference date 2023-06-14 REACH Candidate Substance Note No	Number of bridged terminals	10	
REACH Reference date 2023-06-14 REACH Candidate Substance Note No	Environmental Product Compliance		
REACH Candidate Substance Note No	REACH Conform	yes	
	REACH Reference date	2023-06-14	
RoHS Conform yes	REACH Candidate Substance Note	No	
	RoHS Conform	yes	

Data sheet 2141.0 AQI 10/6/11 YE



Media

Data sheet

2141.0 AQI 10/6/11 YE



Accessories

##INVERSE##CONTA-CONNECT



Feed-through terminal for direct mount, Screw connection, Mounting type: Mounting surface, Rated cross-section: 4 mm², Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
2341.2	BKA 4/20 e.B. BG	4044211051266	10 ST



Feed-through terminal for direct mount, Screw connection, Mounting type: Mounting surface, Rated cross-section: 4 mm², Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
2331.2	BKA 4/5 e.B. BG	4044211051167	50 ST



Feed-through terminal for direct mount, Screw connection, Mounting type: Mounting surface, Rated cross-section: 4 mm², Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
2334.2	BKA 4/10 e.B. BG	4044211051198	20 ST



Feed-through terminal for direct mount, Screw connection, Mounting type: Mounting surface, Rated cross-section: 4 mm², Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
2342.2	BKA 4/24 e.B. BG	4044211051273	10 ST



Feed-through terminal for direct mount, Screw connection, Mounting type: Mounting surface, Rated cross-section: 4 mm², Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
2351.2	BKA 4/13 b.B. BG	4044211051365	20 ST



Article number	Article name	GTIN (EAN)	Packaging unit
<u>2177.2</u>	BKA 4/12 BG	4044211049997	20 ST





Feed-through terminal for direct mount, Screw connection, Mounting type: Mounting surface, Rated cross-section: 4 mm², Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
2344.2	BKA 4/3 b.B. BG	4044211051297	50 ST



Feed-through terminal for direct mount, Screw connection, Mounting type: Mounting surface, Rated cross-section: 4 mm², Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
2349.2	BKA 4/10 b.B. BG	4044211051341	20 ST



Feed-through terminal for direct mount, Screw connection, Mounting type: Mounting surface, Rated cross-section: 4 mm², Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
2356.2	BKA 4/20 b.B. BG	4044211051419	10 ST



Feed-through terminal for direct mount, Screw connection, Mounting type: Mounting surface, Rated cross-section: 4 mm², Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
2335.2	BKA 4/12 e.B. BG	4044211051204	20 ST



Feed-through terminal for direct mount, Screw connection, Mounting type: Mounting surface, Rated cross-section: 4 mm², Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
2346.2	BKA 4/5 b.B. BG	4044211051310	50 ST



Article number	Article name	GTIN (EAN)	Packaging unit
2347.2	BKA 4/6 b.B. BG	4044211051327	50 ST





Feed-through terminal for direct mount, Screw connection, Mounting type: Mounting surface, Rated cross-section: 4 mm², Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
2354.2	BKA 4/16 b.B. BG	4044211051396	20 ST



Feed-through terminal for direct mount, Screw connection, Mounting type: Mounting surface, Rated cross-section: 4 mm², Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
1039.2	BKA 4/24 BG	4044211008284	10 ST



Feed-through terminal for direct mount, Screw connection, Mounting type: Mounting surface, Rated cross-section: 4 mm², Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
2179.2	BKA 4/20 BG	4044211050016	10 ST



Feed-through terminal for direct mount, Screw connection, Mounting type: Mounting surface, Rated cross-section: 4 mm², Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
2339.2	BKA 4/16 e.B. BG	4044211051242	20 ST



Feed-through terminal for direct mount, Screw connection, Mounting type: Mounting surface, Rated cross-section: 4 mm², Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
2309.2	BKA 4/3 e.B. BG	4044211050962	50 ST



Article number	Article name	GTIN (EAN)	Packaging unit
2337.2	BKA 4/14 e.B. BG	4044211051228	20 ST





Feed-through terminal for direct mount, Screw connection, Mounting type: Mounting surface, Rated cross-section: 4 mm², Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
2340.2	BKA 4/18 e.B. BG	4044211051259	20 ST



Feed-through terminal for direct mount, Screw connection, Mounting type: Mounting surface, Rated cross-section: 4 mm², Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
2348.2	BKA 4/8 b.B. BG	4044211051334	20 ST



Feed-through terminal for direct mount, Screw connection, Mounting type: Mounting surface, Rated cross-section: 4 mm², Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
2352.2	BKA 4/14 b.B. BG	4044211051372	20 ST



Feed-through terminal for direct mount, Screw connection, Mounting type: Mounting surface, Rated cross-section: 4 mm², Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
2353.2	BKA 4/15 b.B. BG	4044211051389	20 ST



Feed-through terminal for direct mount, Screw connection, Mounting type: Mounting surface, Rated cross-section: 4 mm², Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
2355.2	BKA 4/18 b.B. BG	4044211051402	20 ST



Article number	Article name	GTIN (EAN)	Packaging unit
<u>1037.2</u>	BKA 4/16 BG	4044211008062	20 ST





Feed-through terminal for direct mount, Screw connection, Mounting type: Mounting surface, Rated cross-section: 4 mm², Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
2171.2	BKA 4/3 BG	4044211049928	50 ST



Feed-through terminal for direct mount, Screw connection, Mounting type: Mounting surface, Rated cross-section: 4 mm², Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
2174.2	BKA 4/6 BG	4044211049959	50 ST



Feed-through terminal for direct mount, Screw connection, Mounting type: Mounting surface, Rated cross-section: 4 mm², Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
2178.2	BKA 4/15 BG	4044211050009	20 ST



Feed-through terminal for direct mount, Screw connection, Mounting type: Mounting surface, Rated cross-section: 4 mm², Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
2332.2	BKA 4/6 e.B. BG	4044211051174	50 ST



Feed-through terminal for direct mount, Screw connection, Mounting type: Mounting surface, Rated cross-section: 4 mm², Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
2333.2	BKA 4/8 e.B. BG	4044211051181	20 ST



Article number	Article name	GTIN (EAN)	Packaging unit
<u>1036.2</u>	BKA 4/14 BG	4044211007959	20 ST





Feed-through terminal for direct mount, Screw connection, Mounting type: Mounting surface, Rated cross-section: 4 mm², Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
2170.2	BKA 4/2 BG	4044211049911	50 ST



Feed-through terminal for direct mount, Screw connection, Mounting type: Mounting surface, Rated cross-section: 4 mm², Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
2172.2	BKA 4/4 BG	4044211049935	50 ST



Feed-through terminal for direct mount, Screw connection, Mounting type: Mounting surface, Rated cross-section: 4 mm², Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
2345.2	BKA 4/4 b.B. BG	4044211051303	50 ST



Feed-through terminal for direct mount, Screw connection, Mounting type: Mounting surface, Rated cross-section: 4 mm², Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
1038.2	BKA 4/18 BG	4044211008178	20 ST



Feed-through terminal for direct mount, Screw connection, Mounting type: Mounting surface, Rated cross-section: 4 mm², Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
2137.2	BKA 4/13 BG	4044211049584	20 ST



Article number	Article name	GTIN (EAN)	Packaging unit
<u>2173.2</u>	BKA 4/5 BG	4044211049942	50 ST





Feed-through terminal for direct mount, Screw connection, Mounting type: Mounting surface, Rated cross-section: 4 mm², Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
2176.2	BKA 4/10 BG	4044211049980	20 ST



Feed-through terminal for direct mount, Screw connection, Mounting type: Mounting surface, Rated cross-section: 4 mm², Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
2343.2	BKA 4/2 b.B. BG	4044211051280	50 ST



Feed-through terminal for direct mount, Screw connection, Mounting type: Mounting surface, Rated cross-section: 4 mm², Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
2357.2	BKA 4/24 b.B. BG	4044211051426	10 ST



Feed-through terminal for direct mount, Screw connection, Mounting type: Mounting surface, Rated cross-section: 4 mm², Width: 6 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
2158.2	BKA 4/1 BG	4044211049782	100



Feed-through terminal for direct mount, Screw connection, Mounting type: Mounting surface, Rated cross-section: 4 mm², Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
2330.2	BKA 4/4 e.B. BG	4044211051150	50 ST



Article number	Article name	GTIN (EAN)	Packaging unit
2336.2	BKA 4/13 e.B. BG	4044211051211	20 ST

Data sheet

2141.0 AQI 10/6/11 YE



##INVERSE##CONTA-CONNECT



Feed-through terminal for direct mount, Screw connection, Mounting type: Mounting surface, Rated cross-section: 4 mm², Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
2350.2	BKA 4/12 b.B. BG	4044211051358	20 ST



Feed-through terminal for direct mount, Screw connection, Mounting type: Mounting surface, Rated cross-section: 4 mm², Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
2308.2	BKA 4/2 e.B. BG	4044211050955	50 ST



Feed-through terminal for direct mount, Screw connection, Mounting type: Mounting surface, Rated cross-section: 4 mm², Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
2338.2	BKA 4/15 e.B. BG	4044211051235	20 ST



Motor-connection terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm², Width: 6 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
1425.2	VMAK 2,5 BG	4044211044701	40 ST

##INVERSE##CONTA-CONNECT



Feed-through terminal for direct mount, Screw connection, Mounting type: Mounting surface, Rated cross-section: 4 mm², Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
2351.2	BKA 4/13 b.B. BG	4044211051365	20 ST

##INVERSE##CONTA-CONNECT

Data sheet 2141.0 AQI 10/6/11 YE





Article number	Article name	GTIN (EAN)	Packaging unit
2177.2	BKA 4/12 BG	4044211049997	20 ST