



External insulated cross-connector, No. of poles: 2, Mounting type: Plug in, Width: 56.13 mm, Rated current: 309 A; Colour: Yellow

### **RAL:** 1026

### **Business data**

Article number	2767.2
Article name	AQI 2/150 YE
GTIN (EAN)	4044211054977
Packaging unit	5
Quantity unit	PC
Weight per piece (not including packaging)	156.8 g
Weight per piece (including packaging)	156.9 g
Unit of weight	G
Customs number	85389099
Country of origin	DE
Prio-Article	2767.2
Product description	External insulated cross-connector



### **Technical data**

Dimensions	
Width	56.13 mm
Pitch size	31 mm
Ratings	
Voltage with partition, max.	1000 V
Voltage without partition, max.	1000 V
Rated current	309 A
Contamination degree	3
Connection data	
No. of poles	2
Materials	
Material	Copper
Surface	Tin-plated
Insulation housing	Polyamide 6.6
Flammability class UL 94	V-2
Working temperature, min.	-40 °C
Working temperature, max.	105 °C
Further technical data	
Mounting type	Plug in
Insulation available	$\checkmark$
Touch protection is available	$\checkmark$
Number of bridged terminals	2
Environmental Product Compliance	
REACH Candidate Substance Note	No

Media





### Accessories

#### ##INVERSE##CONTA-CONNECT



Feed-through terminal to mounting surface, Screw connection, Mounting type: Mounting surface, Rated cross-section: 150 mm<sup>2</sup>, Width: 31 mm, Colour: Beige

A	Article number	Article name	GTIN (EAN)	Packaging unit
1	584.2	RK 150-D BG	4044211047740	5



Ex feed-through terminal ATEX-certified, Screw connection, Mounting type:Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 150 mm<sup>2</sup>, Width: 31 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
1477.2	RK 150 Ex BG	4044211107864	5



Feed-through terminal, Screw connection, Mounting type:Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 150 mm<sup>2</sup>, Width: 31 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
1124.2	RK 150 BG	4044211019198	5