Data sheet 2765.2 AQI 2/95 YE





External insulated cross-connector, No. of poles: 2, Mounting type: Plug in, Width: 44.86 mm, Rated current: 232 A; Colour: Yellow

RAL: 1026

Business data

Article number	2765.2
Article name	AQI 2/95 YE
GTIN (EAN)	4044211054953
Packaging unit	5
Quantity unit	PC
Weight per piece (not including packaging)	93 g
Weight per piece (including packaging)	93.4 g
Unit of weight	G
Customs number	85389099
Country of origin	DE
Prio-Article	2765.2
Product description	External insulated cross-connector

Data sheet





Technical data		
Dimensions		
Width	44.86 mm	
Pitch size	25 mm	
Ratings		
Voltage with partition, max.	1000 V	
Voltage without partition, max.	1000 V	
Rated current	232 A	
Contamination degree	3	
Connection data		
No. of poles	2	
Materials		
Material	Copper	
Surface	Tin-plated	
Insulation housing	Polyamide 6.6	
Flammability class UL 94	V-2	
Working temperature, min.	-40 °C	
Working temperature, max.	105 °C	
Further technical data		
Mounting type	Plug in	
Insulation available	✓	
Touch protection is available	✓	
Number of bridged terminals	2	
Environmental Product Compliance		
REACH Candidate Substance Note	No	

Data sheet 2765.2 AQI 2/95 YE



Media

Data sheet

2765.2 AQI 2/95 YE



Accessories

##INVERSE##CONTA-CONNECT



Feed-through terminal, Screw connection, Mounting type:Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 95 mm², Width: 25 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
1122.2	RK 95 BG	4044211018979	10



Feed-through terminal for direct mount, Screw connection, Mounting type: Mounting surface, Rated cross-section: 95 mm², Width: 25 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
<u>1583.2</u>	RK 95-D BG	4044211047726	10



Ex feed-through terminal ATEX-certified, Screw connection, Mounting type:Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 95 mm², Width: 25 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
1476.2	RK 95 Ex BG	4044211107918	10