Data sheet 2770.2 AQI 3/240 YE





External insulated cross-connector, No. of poles: 3, Mounting type: Plug in, Width: 103.12 mm, Rated current: 380 A; Colour: Yellow

RAL: 1026

Business data

Dusiness data	
Article number	<u>2770.2</u>
Article name	AQI 3/240 YE
GTIN (EAN)	4044211055004
Packaging unit	5
Quantity unit	PC
Weight per piece (not including packaging)	317.84 g
Weight per piece (including packaging)	319.2 g
Unit of weight	G
Customs number	85389099
Country of origin	DE
Prio-Article	2770.2
Product description	External insulated cross-connector

Data sheet





103.12 mm	
36 mm	
1000 V	
1000 V	
380 A	
3	
3	
Copper	
Tin-plated	
Polyamide 6.6	
V-2	
-40 °C	
105 °C	
Plug in	
✓	
✓	
3	
No	
• • • • • • • • • • • • • • • • • • • •	36 mm 1000 V 1000 V 380 A 3 Copper Tin-plated Polyamide 6.6 V-2 -40 °C 105 °C Plug in V 3

Data sheet 2770.2 AQI 3/240 YE



Media

Data sheet

2770.2 AQI 3/240 YE



Accessories

##INVERSE##CONTA-CONNECT



Feed-through terminal, Screw connection, Mounting type:Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 240 mm², Width: 36 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
1126.2	RK 240 BG	4044211019419	5



Ex feed-through terminal ATEX-certified, Screw connection, Mounting type:Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 240 mm², Width: 36 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
1485.2	RK 240 Ex BG	4044211107888	5



Feed-through terminal for direct mount, Screw connection, Mounting surface, Rated cross-section: 240 mm², Width: 36 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
<u>1585.2</u>	RK 240-D BG	4044211047764	5