



Mounting screw, M 2.5, Colour: Violet

Business data

2243.0
BS 25 VT
4044211050665
50
PC
2.85 g
2.86 g
G
74153300
DE
Mounting screw
Violet



Technical dataDimensions7 mmConnection data5 lottedScrew headSlottedScrew threadingM 2,5Tightening torque, min.0.4 NmTightening torque, max.0.8 Nm	
Outer diameter7 mmConnection dataScrew headSlottedScrew threadingM 2,5Tightening torque, min.0.4 Nm	
Connection dataScrew headSlottedScrew threadingM 2,5Tightening torque, min.0.4 Nm	
Screw headSlottedScrew threadingM 2,5Tightening torque, min.0.4 Nm	
Screw threadingM 2,5Tightening torque, min.0.4 Nm	
Tightening torque, min. 0.4 Nm	
Tightening torque, max. 0.8 Nm	
Materials	
Insulation housing Polyamic	le 6.6
Flammability class UL 94 V-2	
Working temperature, min40 °C	
Working temperature, max. 105 °C	
Surface screw Nickel	
Further technical data	
Mounting type Screwab	le
Insulation available ✓	
Environmental Product Compliance	
REACH Conform No	
REACH Reference date 2023-06-	14
REACH Candidate Substance Note No	
REACH CAS 1 Substance LEAD	
REACH CAS 1 Percent minimal 0.1 %	
REACH CAS 1 Percent maximum 4 %	
REACH CAS 1 Number 7439-92-	1
RoHS Conform yes	
RoHS Exception rule 6c	



Media





Accessories

Data sheet

2243.0 BS 25 VT



##INVERSE##CONTA-CONNECT

Test disconnect terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 6 mm², Width: 8.1 mm, Colour: Beige



Article number	Article name	GTIN (EAN)	Packaging unit
17523.2	SPTK 6/LT/HB BG	4044211209223	50 ST

Test disconnect terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 6 mm², Width: 8.1 mm, Colour: Beige



Test disconnect terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 6 mm², Width: 8.1 mm, Colour: Beige



Test disconnect terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 6 mm², Width: 8.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
17521.2	SPTK 6/LT BG	4044211209162	50 ST

Test disconnect terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 6 mm², Width: 8.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
17522.2	SPTK 6/QT BG	4044211209216	50 ST

Test disconnect terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 6 mm², Width: 8.1 mm, Colour: Beige

	Article number	Article name	GTIN (EAN)	Packaging unit
	17525.2	SPTK 6/LT/STBI/BU BG	4044211209926	50 ST



##INVERSE##CONTA-CONNECT

Test disconnect terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5,

Rated cross-section: 6 mm², Width: 8.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
17521.2	SPTK 6/LT BG	4044211209162	50 ST