



Insulated cross-connector, No. of poles: 5, Mounting type: Plug in, Width: 20.4 mm, Colour: Yellow

RAL: 1026

Business data

<u>3455.8</u>
FQI 1,5/5 YE
4044211110673
20
PC
2.4 g
2.5 g
G
85389099
CZ
3455.8
Insulated cross-connector



Technical data

Dimensions	
Length	4 mm
Width	20.4 mm
Pitch size	4.1 mm
Ratings	
Max. voltage	800 V
Rated current	17.5 A
Current load, max.	17,5 A
Rated cross-section	1.5 mm ²
Connection data	
No. of poles	5
Materials	
Material	Copper
Surface	Tin-nickel
Insulation housing	Polyamide 6.6
Flammability class UL 94	V-2
Working temperature, min.	-40 °C
Working temperature, max.	105 °C
Further technical data	
Mounting type	Plug in
Insulation available	\checkmark
Touch protection is available	\checkmark
Number of bridged terminals	5
Environmental Product Compliance	
REACH Candidate Substance Note	No

Media





Accessories

##INVERSE##CONTA-CONNECT

	Feed-through terminal, Push-in connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 1.5 mm², Width: 4.1 mm, Colour: Beige			
1 2. 2. 11. 2. 2. 1	Article number	Article name	GTIN (EAN)	Packaging unit
	3202.2	FRK 1,5/4A BG	4044211109684	100
	Feed-through terminal, Push-in connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 1.5 mm², Width: 4.1 mm, Colour: Beige			
6	Article number	Article name	GTIN (EAN)	Packaging unit
	3200.2	FRK 1,5/2A BG	4044211109530	100
	0	erminal, Push-in connection, Mounting ection: 1.5 mm², Width: 4.1 mm, Colou	5 51 0	35/7.5,



Article number	Article name	GTIN (EAN)	Packaging unit
3201.2	FRK 1,5/3A BG	4044211109615	100

##INVERSE##CONTA-CONNECT



Feed-through terminal, Push-in connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 1.5 mm², Width: 4.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
3201.2	FRK 1,5/3A BG	4044211109615	100