### **Data sheet**

## 3464.8 FQI 2,5/4 YE





Insulated cross-connector, No. of poles: 4, Mounting type: Plug in, Width: 20.3 mm, Colour: Yellow

**RAL:** 1026

#### **Business data**

| Article number                             | 3464.8                    |
|--|---------------------------|
| Article name                               | FQI 2,5/4 YE              |
| GTIN (EAN)                                 | 4044211110758             |
| Packaging unit                             | 20                        |
| Quantity unit                              | PC                        |
| Weight per piece (not including packaging) | 2.6 g                     |
| Weight per piece (including packaging)     | 2.7 g                     |
| Unit of weight                             | G                         |
| Customs number                             | 85389099                  |
| Country of origin                          | CZ                        |
| Prio-Article                               | 3464.8                    |
| Product description                        | Insulated cross-connector |
|  |                           |

## **Data sheet**





| Dimensions                       |                     |  |
|----------------------------------|---------------------|--|
| <b>Dimensions</b> Length         | 4 mm                |  |
| Width                            | 20.3 mm             |  |
|                                  |                     |  |
| Pitch size                       | 5.1 mm              |  |
| Ratings                          |                     |  |
| Max. voltage                     | 800 V               |  |
| Rated current                    | 24 A                |  |
| Current load, max.               | 24 A                |  |
| Rated cross-section              | 2.5 mm <sup>2</sup> |  |
| Connection data                  |                     |  |
| No. of poles                     | 4                   |  |
| Materials                        |                     |  |
| Material                         | Copper              |  |
| Surface                          | Tin-nickel          |  |
| Insulation housing               | Polyamide 6.6       |  |
| Flammability class UL 94         | V-2                 |  |
| Working temperature, min.        | -40 °C              |  |
| Working temperature, max.        | 105 °C              |  |
| Further technical data           |                     |  |
| Mounting type                    | Plug in             |  |
| Insulation available             | ✓                   |  |
| Touch protection is available    | ✓                   |  |
| Number of bridged terminals      | 4                   |  |
| Environmental Product Compliance |                     |  |
| REACH Candidate Substance Note   | No                  |  |

# Data sheet

3464.8 FQI 2,5/4 YE



Media