



Insulated cross-connector, No. of poles: 7, Mounting type: Plug in, Width: 35.6 mm, Colour: Yellow

RAL: 1026

Business data

| | |
|--|---------------------------|
| Article number | 3467.8 |
| Article name | FQI 2,5/7 YE |
| GTIN (EAN) | 4044211110789 |
| Packaging unit | 20 |
| Quantity unit | PC |
| Weight per piece (not including packaging) | 4.6 g |
| Weight per piece (including packaging) | 4.7 g |
| Unit of weight | G |
| Customs number | 85389099 |
| Country of origin | CZ |
| Prio-Article | 3467.8 |
| Product description | Insulated cross-connector |

Technical data

Dimensions

| | |
|------------|---------|
| Length | 4 mm |
| Width | 35.6 mm |
| Pitch size | 5.1 mm |

Ratings

| | |
|---------------------|---------------------|
| Max. voltage | 800 V |
| Rated current | 24 A |
| Current load, max. | 24 A |
| Rated cross-section | 2.5 mm ² |

Connection data

| | |
|--------------|---|
| No. of poles | 7 |
|--------------|---|

Materials

| | |
|---------------------------|---------------|
| Material | Copper |
| Surface | Tin-nickel |
| Insulation housing | Polyamide 6.6 |
| Flammability class UL 94 | V-2 |
| Working temperature, min. | -40 °C |
| Working temperature, max. | 105 °C |

Further technical data

| | |
|-------------------------------|---------|
| Mounting type | Plug in |
| Insulation available | ✓ |
| Touch protection is available | ✓ |
| Number of bridged terminals | 7 |

Environmental Product Compliance

| | |
|--------------------------------|----|
| REACH Candidate Substance Note | No |
|--------------------------------|----|

Data sheet

3467.8 FQI 2,5/7 YE



Media
