





KV Circuit breaker boxes for outdoor installation (harsh environment and/or outdoor)



KV PC 8104

- 4.5 modules: 1 x 4.5 x 18 mm
- without PE and N terminal






- 1-row
- box walls without knockouts
- order PE/N terminals separately
- for indoor (normal environment and/or protected outdoor) and outdoor installation (harsh environment and/or outdoor)
- for the installation of DIN rail equipment up to 63 A, top hat profile 35 mm
- with transparent lid, sealable
- locking device for hinged lid and sealing facility see accessories
- with cable entry cover
- protective cover can be cut out
- degree of protection: IP 65
- colour: grey, RAL 7035


rated insulation voltage	U _i = 400 V a.c. U _i = 1000 V d.c.
power dissipation capability	P _{de} = 12 watts at 30 K according to EN 60670-24
protection class	II
material	PC (Polycarbonate)
width	126 mm
height	228 mm
depth	111 mm
weight	0,627 kg

Drawings

Dimension drawing



Detail mass



Operating and ambient conditions

Application area	Suitable for outdoor installation (harsh environment and/or outdoor). However, pay attention to the climatic effects on the installed equipment, for example, high or low ambient temperatures or formation of condensed water see technical information
Ambient temperature	Average value over 24 hours + 35 °C Maximum value + 40 °C Minimum value - 5 °C
Fire protection in the event of internal faults	Demands placed on electrical devices from standards and laws Minimum requirements - Glow wire test in accordance with IEC 60695-2-11: - 650°C for boxes and cable glands - 850°C for parts of insulating material necessary to retain current carrying parts in position
Burning behaviour	Glow wire test IEC 60695-2-11: 960 °C UL Subject 94: V-2 flame-retardant self-extinguishing
Degree of protection against mechanical load	IK08 (5 Joule)

Toxic behaviour

halogen-free
silicone-free
"halogen-free" in accordance with the examination of the
cables and insulated wires - corrosiveness of fumes - as
per IEC 60754-2

Note:

For material properties see technical data.