

## MFD 50/25/050

Multiple sealing insert



Products may differ in size, colour and appearance to those shown. If you require further information or customisation, please contact us directly.



<b>Material</b>	Thermoplastic elastomer
<b>Temp. range min</b>	-40 °C
<b>Temp. range max</b>	100 °C
<b>Protection class</b>	IP66 / IP68
<b>Ø cable diameter min</b>	4 mm
<b>Ø cable diameter max</b>	5 mm
<b>Quantity of cable</b>	25
<b>BxL</b>	43,6 x 22,9 mm
<b>Product Color</b>	RAL 9005
<b>Using for cable gland</b>	SPRINT 50
<b>Order no. RAL 9005</b>	10063102
<b>Type</b>	MFD 50/25/050
<b>Packing unit</b>	25
<b>EAN number</b>	4007685631020
<b>Tariff number</b>	39269097
<b>ETIM-Classification</b>	EC000441

Remarks:

IP68: Ø cable diameter min. = Ø cable diameter max. - 10%, but not bigger than 1 mm under the Ø cable diameter max.

IP66: 25 cables Ø 4 - 5 mm

11.12.2023

Your Contact:

**WISKA Hoppmann GmbH**

Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany

☎ +49-4191-508-0 · 📠 +49-4191-508-209

contact@wiska.de · www.wiska.com