

MFD 63/01/131-01/118-03/084-02/064

Multiple sealing insert



Products may differ in size, colour and appearance to those shown. If you require further information or customisation, please contact us directly.



Material	Thermoplastic elastomer
Temp. range min	-40 °C
Temp. range max	100 °C
Protection class	IP66 / IP68
Ø cable diameter min	5 mm
Ø cable diameter max	13,1 mm
Quantity of cable	7
BxL	56,4 x 24,3 mm
Product Color	RAL 9005
Using for cable gland	SPRINT 63
Order no. RAL 9005	10101114
Type	MFD 63/01/131-01/118-03/084-02/064
Packing unit	25
EAN number	4007685010177
Tariff number	39269097
ETIM-Classification	EC000441

Remarks:

IP68: Ø cable diameter min. = Ø cable diameter max. - 10%, but not bigger than 1 mm under the Ø cable diameter max.

IP66: for 1 cable 11-13,10mm Ø

for 1 cable 10-11,80mm Ø

for 2 cables 5-6,4mm Ø

for 3 cables 7-8,4mm Ø

11.12.2023

Your Contact:

WISKA Hoppmann GmbH

Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany

☎ +49-4191-508-0 · 📠 +49-4191-508-209

contact@wiska.de · www.wiska.com