


MRM 25/16

Reduction adaptor, brass nickel-plated, M25/M16



Products may differ in size, colour and appearance to those shown. If you require further information or customisation, please contact us directly.



Material	Brass nickel-plated
Temp. range min	-200 °C
Temp. range max	250 °C
Thread type outer	M
Ø outer thread	25
Lead outer	1,5
Length screw-in thread L	7 mm
Thread type inner	M
Ø inner thread	16
Lead inner	1,5
External diameter ED	30 mm
Total length TL	10 mm
Surface	Nickel-plated
Order no. nickel-plated	10063943
Type	MRM 25/16
Packing unit	50
EAN number	4007685639439
Tariff number	74198090
ETIM-Classification	EC000938

Recommended accessories

EMMU 25	10063144
ORD-E 25	10064700

Your Contact:

WISKA Hoppmann GmbH


Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany

☎ +49-4191-508-0 · 📠 +49-4191-508-209

contact@wiska.de · www.wiska.com

11.12.2023

Your Contact:
WISKA Hoppmann GmbH
Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany
☎ +49-4191-508-0 · 📠 +49-4191-508-209
contact@wiska.de · www.wiska.com



Your Contact:
WISKA Hoppmann GmbH
Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany
☎ +49-4191-508-0 · 📠 +49-4191-508-209
contact@wiska.de · www.wiska.com