



Insulated cross-connector, No. of poles: 20, Mounting type: Plug in, Width: 159.4 mm, Colour: Red

Business data

27161.9
PQI 6/20 RD
4044211225391
PC
33.14 g
33.34 g
G
85389099
DE
27161.9
Insulated cross-connector

Data sheet 27161.9 PQI 6/20 RD



Technical data

4 mm
159.4 mm
22.5 mm
8.1 mm
800 V
41 A
41 A
6 mm²
3
20
Polyamide 6.6
V-0
-40 °C
120 °C
Plug in
\checkmark
\checkmark
20
No

Data sheet 27161.9 PQI 6/20 RD

Media



Data sheet 27161.9 PQI 6/20 RD



Accessories

##INVERSE##CONTA-CONNECT

	Protective earth terminal, Push-in connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 6 mm², Width: 8.1 mm, Colour: Green-yellow				
	Article number	Article name	GTIN (EAN)	Packaging unit	
	27021.2	PSL 6/3A GNYE	4044211223960	50 ST	
		n terminal, Push-in connection, Mountin ection: 6 mm², Width: 8.1 mm, Colour: G	0) 1	S 35/7.5,	
	Article number	Article name	GTIN (EAN)	Packaging unit	
	27023.2	PSL 6/4A GNYE	4044211224004	50 ST	
		n terminal, Push-in connection, Mountin ection: 6 mm², Width: 8.1 mm, Colour: G	0) 1	S 35/7.5,	
	Article number	Article name	GTIN (EAN)	Packaging unit	
	27019.2	PSL 6/2A GNYE	4044211223922	50 ST	
	U	erminal, Push-in connection, Mounting tection: 6 mm², Width: 8.1 mm, Colour: G	, i	35/7.5,	
	Article number	Article name	GTIN (EAN)	Packaging unit	
	27018.6	PRK 6/2A GR	4044211223915	50	