



Plug-in miniature power relay, With power contact, 1 CO contact, Input voltage: 60 VDC

Business data	
Article number	<u>15503.2</u>
Article name	PRC 1/60V DC
GTIN (EAN)	4044211118167
Packaging unit	10
Quantity unit	PC
Weight per piece (not including packaging)	5 g
Weight per piece (including packaging)	6.38 g
Unit of weight	G
Customs number	85364900
Country of origin	ES
Product description	Plug-in relay



Technical data

Length 28 mm Width 5 mm Height 15 mm Ratings	Dimensions	
Height 15 mm Ratings Overvoltage category III Contamination degree 3 (250 VAC) / 2 (400 VAC) Input data Vorking voltage 42-90 VDC - Holding current 0,4 Un - Drop-out voltage 0.05 Un Coil voltage 0,05 Un Coil voltage 60 VDC - Power consumption 0,176 W Coil voltage 20500 Ohm Output data Switching voltage / switching voltage max. 250 / 400 VAC Continuous current max. / Inrush current max. 6 / 10 A Contact configuration 1 CO contact Switching capacity, max. 1500 VA Electrical lifespan (AC1) 60x10 ³ Mechanical lifespan 10x10 ^a Contact load, min. 500 mW Bounce time at close of the NO/NC contact 3/8 ms Materials Contact material AgNi Working temperature, max. 85 °C Further technical data Degree of protection RTIII (wash-tight) Insulation voltage coil/contact 4 KV Response/release time 12 / 5 ms Insulation voltage contact/contact 1 kV	Length	28 mm
Ratings Overvoltage category III Contamination degree 3 (250 VAC) / 2 (400 VAC) Input data Working voltage 42-90 VDC - Holding current 0,4 Un - Drop-out voltage 0,05 Un Coil resistance 20500 Ohm Output data Contact configuration Switching voltage / switching voltage max. 250 / 400 VAC Contract configuration 1 CO contact Switching capacity, max. 1500 VA Electrical lifespan 10x10 ^s Contact configuration 1 CX 0 ^s Contact load, min. 500 mW Bounce time at close of the NO/NC contact 3/8 ms Materials Contact material Vorking temperature, max. 85 °C	Width	5 mm
Overvoltage categoryIIIContamination degree3 (250 VAC) / 2 (400 VAC)Input dataWorking voltage42-90 VDC -Holding current0,4 Un -Drop-out voltage0,05 UnCoil voltage60 VDC -Power consumption0,176 WCoil resistance20500 OhmOutput dataSwitching voltage / switching voltage max.250 / 400 VACContact configuration1 CO contactSwitching capacity, max.1500 VAElectrical lifespan (AC1)60×10 ³ Mechanical lifespan10×10 ⁶ Contact load, min.500 mWBounce time at close of the NO/NC contact3/8 msMaterialsContact dataWorking temperature, min40 °CWorking temperature, max.85 °CFurther technical dataRTIII (wash-tight)Insulation voltage coil/contact4 kVResponse/release time12 / 5 msInsulation voltage coil/contact1 kVVibration resistance NO/NC10/5 g	Height	15 mm
Contamination degree 3 (250 VAC) / 2 (400 VAC) Input data Working voltage 42-90 VDC - Holding current 0,4 Un - Drop-out voltage 0,05 Un Coil voltage 60 VDC - Power consumption 0,176 W Coil resistance 20500 Ohm Output data	Ratings	
Input data Vorking voltage Holding current Drop-out voltage 0,4 Un - Drop-out voltage 0,05 Un Coil voltage 60 VDC - Power consumption 0,176 W Coil resistance 20500 Ohm Output data Switching voltage / switching voltage max. 250 / 400 VAC Contact configuration 1 CO contact Switching capacity, max. Electrical lifespan (AC1) 60x10 ³ Mechanical lifespan 10x10 ⁶ Contact load, min. Bounce time at close of the NO/NC contact 3/8 ms Materials Contact material AgNi Working temperature, min. -40 °C Working temperature, max. 85 °C Further technical data Degree of protection RTIII (wash-tight) Insulation voltage coil/contact 4 kV Response/release time 12 / 5 ms Insulation voltage contact/contact 1 kV	Overvoltage category	III
Working voltage42-90 VDC -Holding current0,4 Un -Drop-out voltage0,05 UnCoil voltage60 VDC -Power consumption0,176 WCoil resistance20500 OhmOutput dataSwitching voltage / switching voltage max.250 / 400 VACContinuous current max. / Inrush current max.6 / 10 AContact configuration1 CO contactSwitching capacity, max.1500 VAElectrical lifespan (AC1)60x10³Mechanical lifespan10x10°Contact load, min.500 mWBounce time at close of the NO/NC contact3/8 msMaterialsContact materialAgNiWorking temperature, max.85 °CFurther technical dataDegree of protectionRTIII (wash-tight)Insulation voltage contact/contact4 kVResponse/release time12 / 5 msInsulation voltage contact/contact1 kVVibration resistance NO/NC10/5 g	Contamination degree	3 (250 VAC) / 2 (400 VAC)
Holding current0,4 Un -Drop-out voltage0,05 UnCoil voltage60 VDC -Power consumption0,176 WCoil resistance20500 OhmOutput dataSwitching voltage / switching voltage max.250 / 400 VACContinuous current max. / Inrush current max.6 / 10 AContact configuration1 CO contactSwitching capacity, max.1500 VAElectrical lifespan (AC1)60x10³Mechanical lifespan10x10°Contact to soft the NO/NC contact3/8 msMaterialsContact materialContact materialAgNiWorking temperature, min40 °CWorking temperature, max.85 °CFurther technical dataETIII (wash-tight)Insulation voltage coll/contact4 kVResponse/release time12 / 5 msInsulation voltage contact/contact1 kVVibration resistance NO/NC10/5 g	Input data	
Drop-out voltage0,05 UnCoil voltage60 VDC -Power consumption0,176 WCoil resistance20500 OhmOutput dataSwitching voltage / switching voltage max.250 / 400 VACContact configuration1 CO contactSwitching capacity, max.1500 VAElectrical lifespan (AC1)60x10³Mechanical lifespan10x10°Contact to soft the NO/NC contact3/8 msMaterialsContact number of the NO/NC contact3/8 msMaterialsContact materialAgNiWorking temperature, min40 °CWorking temperature, max.85 °CFurther technical dataRTIII (wash-tight)Insulation voltage coll/contact4 kVResponse/release time12 / 5 msInsulation voltage contact/contact1 kVVibration resistance NO/NC10/5 g	Working voltage	42-90 VDC -
Coil voltage60 VDC -Power consumption0,176 WCoil resistance20500 OhmOutput dataSwitching voltage / switching voltage max.250 / 400 VACContinuous current max. / Inrush current max.6 / 10 AContact configuration1 CO contactSwitching capacity, max.1500 VAElectrical lifespan (AC1)60x10³Mechanical lifespan10x10 ⁶ Contact load, min.500 mWBounce time at close of the NO/NC contact3/8 msMaterialsContact materialAgNiWorking temperature, min40 °CWorking temperature, max.85 °CFurther technical dataRTIII (wash-tight)Insulation voltage coil/contact4 kVResponse/release time12 / 5 msInsulation voltage contact/contact1 kVVibration resistance NO/NC10/5 g	Holding current	0,4 Un -
Power consumption0,176 WCoil resistance20500 OhmOutput data	Drop-out voltage	0,05 Un
Coil resistance20500 OhmOutput dataSwitching voltage / switching voltage max.250 / 400 VACContinuous current max. / Inrush current max.6 / 10 AContact configuration1 CO contactSwitching capacity, max.1500 VAElectrical lifespan (AC1)60x10³Mechanical lifespan10x10°Contact load, min.500 mWBounce time at close of the NO/NC contact3/8 msMaterialsContact materialContact materialAgNiWorking temperature, min40 °CWorking temperature, max.85 °CFurther technical dataTill (wash-tight)Insulation voltage coil/contact4 kVResponse/release time12 / 5 msInsulation voltage contact/contact1 kVVibration resistance NO/NC10/5 g	Coil voltage	60 VDC -
Output data Switching voltage / switching voltage max. 250 / 400 VAC Continuous current max. / Inrush current max. 6 / 10 A Contact configuration 1 CO contact Switching capacity, max. 1500 VA Electrical lifespan (AC1) 60x10° Mechanical lifespan 10x10° Contact load, min. 500 mW Bounce time at close of the NO/NC contact 3/8 ms Materials	Power consumption	0,176 W
Switching voltage / switching voltage max.250 / 400 VACContinuous current max. / Inrush current max.6 / 10 AContact configuration1 CO contactSwitching capacity, max.1500 VAElectrical lifespan (AC1)60x10³Mechanical lifespan10x10°Contact load, min.500 mWBounce time at close of the NO/NC contact3/8 msMaterialsContact materialContact materialAgNiWorking temperature, min40 °CWorking temperature, max.85 °CFurther technical dataDegree of protectionRTIII (wash-tight)Insulation voltage coil/contact1 kVVibration resistance NO/NC10/5 g	Coil resistance	20500 Ohm
Contact configuration6 / 10 AContact configuration1 CO contactSwitching capacity, max.1500 VAElectrical lifespan (AC1)60x10³Mechanical lifespan10x10°Contact load, min.500 mWBounce time at close of the NO/NC contact3/8 msMaterialsContact materialContact materialAgNiWorking temperature, min40 °CWorking temperature, max.85 °CFurther technical dataDegree of protectionRTIII (wash-tight)Insulation voltage coil/contact4 kVResponse/release time12 / 5 msInsulation voltage contact/contact1 kVVibration resistance NO/NC10/5 g	Output data	
Contact configuration1 CO contactSwitching capacity, max.1500 VAElectrical lifespan (AC1)60x10³Mechanical lifespan10x10°Contact load, min.500 mWBounce time at close of the NO/NC contact3/8 msMaterialsContact materialContact materialAgNiWorking temperature, min40 °CWorking temperature, max.85 °CFurther technical dataTIII (wash-tight)Degree of protectionRTIII (wash-tight)Insulation voltage coil/contact1 kVVibration resistance NO/NC10/5 g	Switching voltage / switching voltage max.	250 / 400 VAC
Switching capacity, max.1500 VAElectrical lifespan (AC1)60x103Mechanical lifespan10x106Contact load, min.500 mWBounce time at close of the NO/NC contact3/8 msMaterialsContact materialContact materialAgNiWorking temperature, min40 °CWorking temperature, max.85 °CFurther technical dataDegree of protectionDegree of protectionRTIII (wash-tight)Insulation voltage coil/contact4 kVResponse/release time12 / 5 msInsulation voltage contact/contact1 kVVibration resistance NO/NC10/5 g	Continuous current max. / Inrush current max.	6 / 10 A
Electrical lifespan (AC1)60x103Mechanical lifespan10x106Contact load, min.500 mWBounce time at close of the NO/NC contact3/8 msMaterialsContact materialAgNiContact materialAgNiWorking temperature, min40 °CWorking temperature, max.85 °CFurther technical dataEnvironmental (wash-tight)Degree of protectionRTIII (wash-tight)Insulation voltage coil/contact4 kVResponse/release time12 / 5 msInsulation voltage contact/contact1 kVVibration resistance NO/NC10/5 g	Contact configuration	1 CO contact
Mechanical lifespan10x10°Contact load, min.500 mWBounce time at close of the NO/NC contact3/8 msMaterialsContact materialAgNiContact materialAgNiWorking temperature, min40 °CWorking temperature, max.85 °CFurther technical dataRTIII (wash-tight)Degree of protectionRTIII (wash-tight)Insulation voltage coil/contact4 kVResponse/release time12 / 5 msInsulation voltage contact/contact1 kVVibration resistance NO/NC10/5 g	Switching capacity, max.	1500 VA
Contact load, min.500 mWBounce time at close of the NO/NC contact3/8 msMaterialsContact materialAgNiWorking temperature, min40 °CWorking temperature, max.85 °CFurther technical dataDegree of protectionRTIII (wash-tight)Insulation voltage coil/contact4 kVResponse/release time12 / 5 msInsulation voltage contact/contact1 kVVibration resistance NO/NC10/5 g	Electrical lifespan (AC1)	60x10 ³
Bounce time at close of the NO/NC contact3/8 msMaterialsAgNiContact materialAgNiWorking temperature, min40 °CWorking temperature, max.85 °CFurther technical dataDegree of protectionRTIII (wash-tight)Insulation voltage coil/contact4 kVResponse/release time12 / 5 msInsulation voltage contact/contact1 kVVibration resistance NO/NC10/5 g	Mechanical lifespan	10x10 ⁶
MaterialsContact materialAgNiWorking temperature, min40 °CWorking temperature, max.85 °CFurther technical dataDegree of protectionRTIII (wash-tight)Insulation voltage coil/contact4 kVResponse/release time12 / 5 msInsulation voltage contact/contact1 kVVibration resistance NO/NC10/5 g	Contact load, min.	500 mW
Contact materialAgNiWorking temperature, min40 °CWorking temperature, max.85 °CFurther technical dataDegree of protectionRTIII (wash-tight)Insulation voltage coil/contact4 kVResponse/release time12 / 5 msInsulation voltage contact/contact1 kVVibration resistance NO/NC10/5 g	Bounce time at close of the NO/NC contact	3/8 ms
Working temperature, min40 °CWorking temperature, max.85 °CFurther technical dataDegree of protectionRTIII (wash-tight)Insulation voltage coil/contact4 kVResponse/release time12 / 5 msInsulation voltage contact/contact1 kVVibration resistance NO/NC10/5 g	Materials	
Working temperature, max.85 °CFurther technical dataDegree of protectionRTIII (wash-tight)Insulation voltage coil/contact4 kVResponse/release time12 / 5 msInsulation voltage contact/contact1 kVVibration resistance NO/NC10/5 g	Contact material	AgNi
Further technical data Degree of protection RTIII (wash-tight) Insulation voltage coil/contact 4 kV Response/release time 12 / 5 ms Insulation voltage contact/contact 1 kV Vibration resistance NO/NC 10/5 g	Working temperature, min.	-40 °C
Degree of protectionRTIII (wash-tight)Insulation voltage coil/contact4 kVResponse/release time12 / 5 msInsulation voltage contact/contact1 kVVibration resistance NO/NC10/5 g	Working temperature, max.	85 °C
Insulation voltage coil/contact4 kVResponse/release time12 / 5 msInsulation voltage contact/contact1 kVVibration resistance NO/NC10/5 g	Further technical data	
Response/release time12 / 5 msInsulation voltage contact/contact1 kVVibration resistance NO/NC10/5 g	Degree of protection	RTIII (wash-tight)
Insulation voltage contact/contact 1 kV Vibration resistance NO/NC 10/5 g	Insulation voltage coil/contact	4 kV
Vibration resistance NO/NC 10/5 g	Response/release time	12 / 5 ms
	Insulation voltage contact/contact	1 kV
Shock resistance NO/NC 10/5 g	Vibration resistance NO/NC	10/5 g
	Shock resistance NO/NC	10/5 g



Technical data

Environmental Product Compliance		
REACH Conform	yes	
REACH Reference date	2023-06-14	
REACH Candidate Substance Note	No	
RoHS Conform	yes	



Approvals


Standards and regulations


CE compliant

yes



Media





ZCONTACLIP

Accessories

##INVERSE##CONTA-ELECTRONICS

			TACLE	•	
	18		DITTACLIP	- Al	
	-	1 월등			2
	2	the state	Ľ,		-
		C € ""	1 ¹⁰ 23	8 - 1	-9
- 1		•			

Interface-Relay-Compact (IRC) socket base IRC with screw connection, Mounting type: Mounting rail TS 35, 1 CO contact, Input voltage: 110 to 125 VAC/DC

Article number	Article name	GTIN (EAN)	Packaging unit
16191.2	IRC 110125V AC/DC	4044211187279	10 ST



Interface-Relay-Compact (IRC) socket base FIRC with Push-In connection, Mounting type: Mounting rail TS 35, 1 CO contact, Input voltage: 110 to 125 VAC/DC

Article number	Article name	GTIN (EAN)	Packaging unit
16211.2	FIRC 110125V AC/DC	4044211187460	10 ST



Interface-Relay-Compact (IRC) socket base FIRC P with Push-In connection, Mounting type: Mounting rail TS 35, 1 CO contact, Input voltage: 60 VAC/DC

Article number	Article name	GTIN (EAN)	Packaging unit
16214.2	FIRCP 60V AC/DC	4044211187491	10 ST



Interface-Relay-Compact (IRC) socket base FIRC P with Push-In connection, Mounting type: Mounting rail TS 35, 1 CO contact, Input voltage: 110 to 125 VAC/DC

Article number	Article name	GTIN (EAN)	Packaging unit
16215.2	FIRCP 110125V AC/DC	4044211187514	10 ST



Interface-Relay-Compact (IRC) socket base FIRC P with Push-In connection, Mounting type: Mounting rail TS 35, 1 CO contact, Input voltage: 230 to 240 VAC/DC

2004 - C	Article number	Article name	GTIN (EAN)	Packaging unit
	<u>16216.2</u>	FIRCP 230240V AC	4044211187507	10 ST



Interface-Relay-Compact (IRC) socket base FIRC P with Push-In connection, Mounting type: Mounting rail TS 35, 1 CO contact, Input voltage: 110 to 125 VDC

Article number	Article name	GTIN (EAN)	Packaging unit
16217.2	FIRCP 110125V DC	4044211187521	10 ST



##INVERSE##CONTA-ELECTRONICS



Interface-Relay-Compact (IRC) socket base IRCI with screw connection, Mounting type: Mounting rail TS 35, 1 CO contact, Input voltage: 110 to 125 VAC/DC

Article number	Article name	GTIN (EAN)	Packaging unit
16202.2	IRCI 110125V AC/DC	4044211187392	10 ST



Interface-Relay-Compact (IRC) socket base IRCO with screw connection, Mounting type: Mounting rail TS 35, 1 CO contact, Input voltage: 230 to 240 VAC/DC

Article number	Article name	GTIN (EAN)	Packaging unit
16206.2	IRCO 230240V AC	4044211187439	10 ST

Interface-Relay-Compact (IRC) socket base FIRC P with Push-In connection, Mounting type: Mounting rail TS 35, 1 CO contact, Input voltage: 220 VDC

Article number	Article name	GTIN (EAN)	Packaging unit
16218.2	FIRCP 220V DC	4044211187538	10 ST

Interface-Relay-Compact (IRC) socket base FIRC P with Push-In connection and residual current suppression for long cables, Mounting type: Mounting rail TS 35, 1 CO contact, Input voltage: 110 to 125 VAC/DC

Article number	Article name	GTIN (EAN)	Packaging unit
16219.2	FIRCP LW 110125V AC/DC	4044211187545	10 ST



Interface-Relay-Compact (IRC) socket base FIRC P with Push-In connection and residual current suppression for long cables, Mounting type: Mounting rail TS 35, 1 CO contact, Input voltage: 230 to 240 VAC/DC

. ~ .	Article number	Article name	GTIN (EAN)	Packaging unit
	16220.2	FIRCP LW 230240V AC	4044211187552	10 ST



Interface-Relay-Compact (IRC) socket base FIRC I with Push-In connection, Mounting type: Mounting rail TS 35, 1 CO contact, Input voltage: 110 to 125 VAC/DC

Article number	Article name	GTIN (EAN)	Packaging unit
16222.2	FIRCI 110125V AC/DC	4044211187576	10 ST



##INVERSE##CONTA-ELECTRONICS



Interface-Relay-Compact (IRC) Complete, Consisting of base IRCO... with screw connection and pluggable miniature relay PRC... with power contact, Mounting type: Mounting rail TS 35, 1 CO contact, Input voltage: 125 VAC/DC

Article number	Article name	GTIN (EAN)	Packaging unit
16253.2	IRCOU 1/125V AC/DC	4044211200350	10 ST



Interface-Relay-Compact (IRC) socket base FIRC O with Push-In connection, Mounting type: Mounting rail TS 35, 1 CO contact, Input voltage: 110 to 125 VAC/DC

Article number	Article name	GTIN (EAN)	Packaging unit
16225.2	FIRCO 110125V AC/DC	4044211187606	10 ST

Interface-Relay-Compact (IRC) socket base IRC with screw connection, Mounting type: Mounting rail TS 35, 1 CO contact, Input voltage: 230 to 240 VAC/DC

Article number	Article name	GTIN (EAN)	Packaging unit
16192.2	IRC 230240V AC	4044211187286	10 ST

Central States

Interface-Relay-Compact (IRC) socket base IRCP with screw connection, Mounting type: Mounting rail TS 35, 1 CO contact, Input voltage: 60 VAC/DC

Article number	Article name	GTIN (EAN)	Packaging unit
16194.2	IRCP 60V AC/DC	4044211187309	10 ST



Interface-Relay-Compact (IRC) socket base IRCP with screw connection, Mounting type: Mounting rail TS 35, 1 CO contact, Input voltage: 110 to 125 VAC/DC

Article number	Article name	GTIN (EAN)	Packaging unit
16195.2	IRCP 110125V AC/DC	4044211187316	10 ST



Interface-Relay-Compact (IRC) socket base IRCP with screw connection, Mounting type: Mounting rail TS 35, 1 CO contact, Input voltage: 230 to 240 VAC/DC

 Article number	Article name	GTIN (EAN)	Packaging unit
16196.2	IRCP 230240V AC	4044211187323	10 ST



##INVERSE##CONTA-ELECTRONICS



Interface-Relay-Compact (IRC) socket base IRCI with screw connection, Mounting type: Mounting rail TS 35, 1 CO contact, Input voltage: 230 to 240 VAC/DC

Article number	Article name	GTIN (EAN)	Packaging unit
16203.2	IRCI 230240V AC	4044211187408	10 ST



Interface-Relay-Compact (IRC) socket base IRCO with screw connection, Mounting type: Mounting rail TS 35, 1 CO contact, Input voltage: 110 to 125 VAC/DC

Article number	Article name	GTIN (EAN)	Packaging unit
16205.2	IRCO 110125V AC/DC	4044211187422	10 ST



Interface-Relay-Compact (IRC) socket base FIRC with Push-In connection, Mounting type: Mounting rail TS 35, 1 CO contact, Input voltage: 230 to 240 VAC/DC

Article number	Article name	GTIN (EAN)	Packaging unit
16212.2	FIRC 230240V AC	4044211187477	10 ST



Interface-Relay-Compact (IRC) socket base FIRC O with Push-In connection, Mounting type: Mounting rail TS 35, 1 CO contact, Input voltage: 230 to 240 VAC/DC

Article number	Article name	GTIN (EAN)	Packaging unit
16226.2	FIRCO 230240V AC	4044211187613	10 ST



Interface-Relay-Compact (IRC) socket base IRCP with screw connection, Mounting type: Mounting rail TS 35, 1 CO contact, Input voltage: 110 to 125 VDC

Article number	Article name	GTIN (EAN)	Packaging unit
<u>16197.2</u>	IRCP 110125V DC	4044211187347	10 ST



Interface-Relay-Compact (IRC) socket base IPRC with screw connection and residual current suppression for long cables, Mounting type: Mounting rail TS 35, 1 CO contact, Input voltage: 230 to 240 VAC/DC

Article number	Article name	GTIN (EAN)	Packaging unit
16200.2	IRCP LW 230240V AC	4044211187378	10 ST



##INVERSE##CONTA-ELECTRONICS



Interface-Relay-Compact (IRC) socket base IPRC with screw connection and residual current suppression for long cables, Mounting type: Mounting rail TS 35, 1 CO contact, Input voltage: 110 to 125 VAC/DC

Article number	Article name	GTIN (EAN)	Packaging unit
16199.2	IRCP LW 110125V AC/DC	4044211187361	10 ST



Interface-Relay-Compact (IRC) socket base IPRC with screw connection and residual current suppression for long cables, Mounting type: Mounting rail TS 35, 1 CO contact, Input voltage: 230 to 240 VAC/DC

Article number	Article name	GTIN (EAN)	Packaging unit
16200.2	IRCP LW 230240V AC	4044211187378	10 ST



Interface-Relay-Compact (IRC) Complete, Consisting of base IRC... with screw connection and pluggable miniature relay PRC... with power contact, Mounting type: Mounting rail TS 35, 1 CO contact, Input voltage: 125 VAC/DC

Article number	Article name	GTIN (EAN)	Packaging unit
16233.2	IRCU 1/125V AC/DC	4044211200176	10 ST



Interface-Relay-Compact (IRC) Complete, Consisting of base IRC... with screw connection and pluggable miniature relay PRC... with power contact, Mounting type: Mounting rail TS 35, 1 CO contact, Input voltage: 240 VAC

Article number	Article name	GTIN (EAN)	Packaging unit
16234.2	IRCU 1/240V AC	4044211200183	10 ST



Interface-Relay-Compact (IRC) Complete, Consisting of base IRCP... with screw connection and pluggable miniature relay PRC... with power contact, Mounting type: Mounting rail TS 35, 1 CO contact, Input voltage: 60 VAC/DC

Article number	Article name	GTIN (EAN)	Packaging unit
16238.2	IRCPU 1/60V AC/DC	4044211200220	10 ST



##INVERSE##CONTA-ELECTRONICS



Interface-Relay-Compact (IRC) Complete, Consisting of base FIRCP... with Push-In connection and pluggable miniature relay with power contact, Mounting type: Mountingrail TS 35, 1 CO contact, Input voltage: 60 VAC/DC

Article number	Article name	GTIN (EAN)	Packaging unit
16268.2	FIRCPU 1/60V AC/DC	4044211200473	10 ST



Interface-Relay-Compact (IRC) Complete, Consisting of base IRCP... with screw connection and pluggable miniature relay PRC... with power contact, Mounting type: Mounting rail TS 35, 1 CO contact, Input voltage: 240 VAC

Article number	Article name	GTIN (EAN)	Packaging unit
16240.2	IRCPU 1/240V AC	4044211200244	10 ST



Interface-Relay-Compact (IRC) Complete, Consisting of base FIRCP... with Push-In connection and pluggable miniature relay with power contact, Mounting type: Mounting rail TS 35, 1 CO contact, Input voltage: 240 VAC

Article number	Article name	GTIN (EAN)	Packaging unit
16270.2	FIRCPU 1/240V AC	4044211200497	10 ST



Interface-Relay-Compact (IRC) Complete, Consisting of base IRCP... with screw connection and pluggable miniature relay PRC... with power contact, Mounting type: Mounting rail TS 35, 1 CO contact, Input voltage: 220 VDC

Article number	Article name	GTIN (EAN)	Packaging unit
16242.2	IRCPU 1/220V DC	4044211200268	10 ST



Interface-Relay-Compact (IRC) Complete, Consisting of base IRCI... with screw connection and pluggable miniature relay PRC... with power contact, Mounting type: Mounting rail TS 35, 1 CO contact, Input voltage: 240 VAC

Article number	Article name	GTIN (EAN)	Packaging unit
16249.2	IRCIU 1/240V AC	4044211200336	10 ST



##INVERSE##CONTA-ELECTRONICS



Interface-Relay-Compact (IRC) Complete, Consisting of base IRCP... with screw connection and pluggable miniature relay PRC... with power contact, Mounting type: Mounting rail TS 35, 1 CO contact, Input voltage: 240 VAC

Article number	Article name	GTIN (EAN)	Packaging unit
16244.2	IRCPU LW 1/240V AC	4044211200282	10 ST



Interface-Relay-Compact (IRC) Complete, Consisting of base IRCO... with screw connection and pluggable miniature relay PRC... with power contact, Mounting type: Mounting rail TS 35, 1 CO contact, Input voltage: 125 VAC/DC

Article number	Article name	GTIN (EAN)	Packaging unit
16253.2	IRCOU 1/125V AC/DC	4044211200350	10 ST



Interface-Relay-Compact (IRC) Complete, Consisting of base IRCO... with screw connection and pluggable miniature relay PRC... with power contact, Mounting type: Mounting rail TS 35, 1 CO contact, Input voltage: 240 VAC

Article number	Article name	GTIN (EAN)	Packaging unit
16254.2	IRCOU 1/240V AC	4044211200367	10 ST



Interface-Relay-Compact (IRC) Complete, Consisting of base FIRC... with Push-In connection and pluggable miniature relay with power contact, Mounting type: Mounting rail TS 35, 1 CO contact, Input voltage: 125 VAC/DC

Article number	Article name	GTIN (EAN)	Packaging unit
16263.2	FIRCU 1/125V AC/DC	4044211200428	10 ST



Interface-Relay-Compact (IRC) Complete, Consisting of base FIRC... with Push-In connection and pluggable miniature relay with power contact, Mounting type: Mounting rail TS 35, 1 CO contact, Input voltage: 240 VAC

Article number	Article name	GTIN (EAN)	Packaging unit
16264.2	FIRCU 1/240V AC	4044211200435	10 ST



##INVERSE##CONTA-ELECTRONICS



Interface-Relay-Compact (IRC) Complete, Consisting of base FIRCP... with Push-In connection and pluggable miniature relay with power contact, Mounting type: Mountingrail TS 35, 1 CO contact, Input voltage: 60 VAC/DC

Article number	Article name	GTIN (EAN)	Packaging unit
16268.2	FIRCPU 1/60V AC/DC	4044211200473	10 ST



Interface-Relay-Compact (IRC) Complete, Consisting of base FIRCP... with Push-In connection and pluggable miniature relay with power contact, Mounting type: Mounting rail TS 35, 1 CO contact, Input voltage: 125 VAC/DC

Article number	Article name	GTIN (EAN)	Packaging unit
16269.2	FIRCPU 1/125V AC/DC	4044211200480	10 ST



Interface-Relay-Compact (IRC) Complete, Consisting of base FIRCP... with Push-In connection and pluggable miniature relay with power contact, Mounting type: Mounting rail TS 35, 1 CO contact, Input voltage: 240 VAC

Article number	Article name	GTIN (EAN)	Packaging unit
16270.2	FIRCPU 1/240V AC	4044211200497	10 ST



Interface-Relay-Compact (IRC) Complete, Consisting of base FIRCP... with Push-In connection and pluggable miniature relay with power contact, Mounting type: Mounting rail TS 35, 1 CO contact, Input voltage: 220 VDC

Article number	Article name	GTIN (EAN)	Packaging unit
16272.2	FIRCPU 1/220V DC	4044211200510	10 ST



Interface-Relay-Compact (IRC) Complete, Consisting of base FIRCP... with Push-In connection and pluggable miniature relay with power contact, Mounting type: Mounting rail TS 35, 1 CO contact, Input voltage: 125 VAC/DC

Article number	Article name	GTIN (EAN)	Packaging unit
16273.2	FIRCPU LW 1/125V AC/DC	4044211200527	10 ST



##INVERSE##CONTA-ELECTRONICS



Interface-Relay-Compact (IRC) Complete, Consisting of base FIRCP... with Push-In connection and pluggable miniature relay with power contact, Mounting type: Mountingrail TS 35, 1 CO contact, Input voltage: 240 VAC

Article number	Article name	GTIN (EAN)	Packaging unit
16274.2	FIRCPU LW 1/240V AC	4044211200534	10 ST



Interface-Relay-Compact (IRC) Complete, Consisting of base IRCI... with screw connection and pluggable miniature relay PRC... with power contact, Mounting type: Mounting rail TS 35, 1 CO contact, Input voltage: 125 VAC/DC

Article number	Article name	GTIN (EAN)	Packaging unit
16248.2	IRCIU 1/125V AC/DC	4044211200329	10 ST



Interface-Relay-Compact (IRC) Complete, Consisting of base IRCI... with screw connection and pluggable miniature relay PRC... with power contact, Mounting type: Mounting rail TS 35, 1 CO contact, Input voltage: 240 VAC

Article number	Article name	GTIN (EAN)	Packaging unit
16249.2	IRCIU 1/240V AC	4044211200336	10 ST



Interface-Relay-Compact (IRC) Complete, Consisting of base FIRCO... with Push-In connection and pluggable miniature relay with power contact, Mounting type: Mounting rail TS 35, 1 CO contact, Input voltage: 125 VAC/DC

Article number	Article name	GTIN (EAN)	Packaging unit
16283.2	FIRCOU 1/125V AC/DC	4044211200626	10 ST



Interface-Relay-Compact (IRC) Complete, Consisting of base FIRCO... with Push-In connection and pluggable miniature relay with power contact, Mounting type: Mounting rail TS 35, 1 CO contact, Input voltage: 240 VAC

Article number	Article name	GTIN (EAN)	Packaging unit
16284.2	FIRCOU 1/240V AC	4044211200633	10 ST



##INVERSE##CONTA-ELECTRONICS



Interface-Relay-Compact (IRC) Complete, Consisting of base FIRCP... with Push-In connection and pluggable miniature relay with power contact, Mounting type: Mountingrail TS 35, 1 CO contact, Input voltage: 125 VDC

Article number	Article name	GTIN (EAN)	Packaging unit
16271.2	FIRCPU 1/125V DC	4044211200503	10 ST



Interface-Relay-Compact (IRC) Complete, Consisting of base FIRCI... with Push-In connection and pluggable miniature relay with power contact, Mounting type: Mounting rail TS 35, 1 CO contact, Input voltage: 125 VAC/DC

Article number	Article name	GTIN (EAN)	Packaging unit
16278.2	FIRCIU 1/125V AC/DC	4044211200572	10 ST



Interface-Relay-Compact (IRC) Complete, Consisting of base FIRCI... with Push-In connection and pluggable miniature relay with power contact, Mounting type: Mounting rail TS 35, 1 CO contact, Input voltage: 240 VAC

Article number	Article name	GTIN (EAN)	Packaging unit
16279.2	FIRCIU 1/240V AC	4044211200589	10 ST



Plug-Relay-Compact (PRC) socket base PRC with tension-spring connection, Mounting type: Mounting rail TS 35, 1 CO contact, Input voltage: 220 to 240 VAC/DC

Article number	Article name	GTIN (EAN)	Packaging unit
15493.2	ZPRC 220240V AC/DC	4044211118334	10 ST



Plug-Relay-Compact (PRC) socket base PRC with screw connection and residual current suppression for long cables, Mounting type: Mounting rail TS 35, 1 CO contact, Input voltage: 110 to 125 VAC/DC

Article number	Article name	GTIN (EAN)	Packaging unit
15555.2	PRC LW 110125V AC/DC	4044211118280	10 ST



##INVERSE##CONTA-ELECTRONICS



Plug-Relay-Compact (PRC) socket base PRC with tension-spring connection andresidual current suppression for long cables, Mounting type: Mounting rail TS 35, 1 COcontact, Input voltage: 110 to 125 VAC/DC

Article number	Article name	GTIN (EAN)	Packaging unit
15556.2	ZPRC LW 110125V AC/DC	4044211118358	10 ST

Plug-Relay-Compact (PRC) socket base PRC with screw connection, Mounting type: Mounting rail TS 35, 1 CO contact, Input voltage: 230 to 240 VAC

Article number	Article name	GTIN (EAN)	Packaging unit
16145.2	PRC 230240V AC	4044211189532	10 ST

Plug-Relay-Compact (PRC) socket base PRC with screw connection, Mounting type: Mounting rail TS 35, 1 CO contact, Input voltage: 220 to 240 VAC/DC

Article number	Article name	GTIN (EAN)	Packaging unit
15489.2	PRC 220240V AC/DC	4044211118259	10 ST



Plug-Relay-Compact (PRC) socket base PRC with screw connection and residual current suppression for long cables, Mounting type: Mounting rail TS 35, 1 CO contact, Input voltage: 220 to 240 VAC

Article number	Article name	GTIN (EAN)	Packaging unit
15491.2	PRC LW 220240V AC	4044211118273	10 ST



Plug-Relay-Compact (PRC) socket base PRC with tension-spring connection and residual current suppression for long cables, Mounting type: Mounting rail TS 35, 1 CO contact, Input voltage: 220 to 240 VAC

Article number	Article name	GTIN (EAN)	Packaging unit
<u>15495.2</u>	ZPRC LW 220240V AC	4044211118365	10 ST



##INVERSE##CONTA-ELECTRONICS



Plug-Relay-Compact (PRC) socket base PRC with screw connection, Mounting type: Mounting rail TS 35, 1 CO contact, Input voltage: 48 or 60 VAC/DC

Article number	Article name	GTIN (EAN)	Packaging unit
15496.2	PRC 48-60V AC/DC	4044211118235	10 ST




Plug-Relay-Compact (PRC) socket base PRC with screw connection, Mounting type: Mounting rail TS 35, 1 CO contact, Input voltage: 110 to 125 VAC/DC

Article number	Article name	GTIN (EAN)	Packaging unit
15497.2	PRC 110125V AC/DC	4044211118242	10 ST

Plug-Relay-Compact (PRC) socket base PRC with tension-spring connection, Mounting type: Mounting rail TS 35, 1 CO contact, Input voltage: 648 or 60 VAC/DC

Article number	Article name	GTIN (EAN)	Packaging unit
15498.2	ZPRC 48-60V AC/DC	4044211118303	10 ST



Article number	Article name	GTIN (EAN)	Packaging unit
15499.2	ZPRC 110125V AC/DC	4044211118327	10 ST



Plug-Relay-Compact (PRC) Complete, Consisting of base PRC... with screw connection and pluggable miniature relay PRC... with power contact, Mounting type: Mounting rail TS 35, 1 CO contact, Input voltage: 60 VAC/DC

80°	Article number	Article name	GTIN (EAN)	Packaging unit
	<u>15510.2</u>	PRCU 1/60V AC/DC	4044211118495	10 ST



Plug-Relay-Compact (PRC) Complete, Consisting of base PRC... with tension-spring connection and pluggable miniature relay PRC... with power contact, Mounting type: Mounting rail TS 35, 1 CO contact, Input voltage: 240 VAC/DC

Article number	Article name	GTIN (EAN)	Packaging unit
15552.2	ZPRCU LW 1/240V AC	4044211118679	10 ST



##INVERSE##CONTA-ELECTRONICS



Plug-Relay-Compact (PRC) Complete, Consisting of base PRC... with screw connection and pluggable miniature relay PRC... with power contact, Mounting type: Mounting rail TS 35, 1 CO contact, Input voltage: 125 VAC/DC

Article number	Article name	GTIN (EAN)	Packaging unit
15511.2	PRCU 1/125V AC/DC	4044211118501	10 ST



Plug-Relay-Compact (PRC) Complete, Consisting of base PRC... with screw connection and pluggable miniature relay PRC... with power contact, Mounting type: Mounting rail TS 35, 1 CO contact, Input voltage: 240 VAC/DC

Article number	Article name	GTIN (EAN)	Packaging unit
15554.2	PRCU LW 1/240V AC	4044211118563	10 ST



Plug-Relay-Compact (PRC) Complete, Consisting of base PRC... with screw connection and pluggable miniature relay PRC... with power contact, Mounting type: Mounting rail TS 35, 1 CO contact, Input voltage: 60 VAC/DC

Article number	Article name	GTIN (EAN)	Packaging unit
15521.2	ZPRCU 1/60V AC/DC	4044211118600	10 ST



Plug-Relay-Compact (PRC) Complete, Consisting of base PRC... with screw connection and pluggable miniature relay PRC... with power contact, Mounting type: Mounting rail TS 35, 1 CO contact, Input voltage: 125 VAC/DC

Article number	Article name	GTIN (EAN)	Packaging unit
15522.2	ZPRCU 1/125V AC/DC	4044211118617	10 ST



Plug-Relay-Compact (PRC) Complete, Consisting of base PRC... with screw connection and pluggable miniature relay PRC... with power contact, Mounting type: Mounting rail TS 35, 1 CO contact, Input voltage: 240 VAC/DC

and	Article number	Article name	GTIN (EAN)	Packaging unit
	15554.2	PRCU LW 1/240V AC	4044211118563	10 ST



##INVERSE##CONTA-ELECTRONICS



Plug-Relay-Compact (PRC) Complete, Consisting of base PRC... with screw connection and pluggable miniature relay PRC... with power contact, Mounting type: Mounting rail TS 35, 1 CO contact, Input voltage: 125 VAC/DC

Article number	Article name	GTIN (EAN)	Packaging unit
15553.2	PRCU LW 1/125V AC/DC	4044211118556	10 ST



Plug-Relay-Compact (PRC) Complete, Consisting of base PRC... with screw connection and pluggable miniature relay PRC... with power contact, Mounting type: Mounting rail TS 35, 1 CO contact, Input voltage: 125 VAC/DC

Article number	Article name	GTIN (EAN)	Packaging unit
15522.2	ZPRCU 1/125V AC/DC	4044211118617	10 ST



Plug-Relay-Compact (PRC) Complete, Consisting of base PRC... with screw connection and pluggable miniature relay PRC... with power contact, Mounting type: Mounting rail TS 35, 1 CO contact, Input voltage: 240 VAC/DC

Article number	Article name	GTIN (EAN)	Packaging unit
15554.2	PRCU LW 1/240V AC	4044211118563	10 ST