



Cross-connector, No. of poles: 2, Mounting type: Can be screwed on, Width: 14.1 mm, Rated cross-section: 10 mm², Colour: natural

Business data

| | |
|--|-----------------|
| Article number | <u>2060.0</u> |
| Article name | Q 2 |
| GTIN (EAN) | 4044211048662 |
| Packaging unit | 50 |
| Quantity unit | PC |
| Weight per piece (not including packaging) | 5.48 g |
| Weight per piece (including packaging) | 5.49 g |
| Unit of weight | G |
| Customs number | 85389099 |
| Country of origin | CZ |
| Product description | Cross-connector |
| Colour | Natural |

Technical data

Dimensions

| | |
|---------------------------------------|---------|
| Length | 6 mm |
| Width | 14.1 mm |
| Hole diameter | 3.4 mm |
| Hole spacing (mid-point to mid-point) | 8.1 mm |
| Pitch size | 8 mm |

Ratings

| | |
|---------------------------------|--------------------|
| Voltage with partition, max. | 800 V |
| Voltage without partition, max. | 400 V |
| Rated current | 47 A |
| Rated cross-section | 10 mm ² |
| Contamination degree | 3 |

Connection data

| | |
|-------------------------|---------|
| No. of poles | 2 |
| Screw head | Slotted |
| Screw threading | M 3 |
| Tightening torque, min. | 0.5 Nm |
| Tightening torque, max. | 1 Nm |

Materials

| | |
|---------------|------------|
| Material | Brass |
| Surface | Nickel |
| Surface screw | Galvanized |

Further technical data

| | |
|-----------------------------|-----------|
| Mounting type | Screwable |
| Number of bridged terminals | 2 |

Technical data

Environmental Product Compliance

| | |
|--------------------------------|------------|
| REACH Conform | No |
| REACH Reference date | 2023-06-14 |
| REACH Candidate Substance Note | No |
| REACH CAS 1 Substance | LEAD |
| REACH CAS 1 Percent minimal | 0.1 % |
| REACH CAS 1 Percent maximum | 4 % |
| REACH CAS 1 Number | 7439-92-1 |
| RoHS Conform | yes |
| RoHS Exception rule | 6c |

Media



Accessories

Screwdriver

Screwdriver with bare blade, Colour: Black-grey



| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|--------------|---------------|----------------|
| <u>1086.0</u> | SDB 0,6x3,5 | 4044211014797 | 1 ST |
