



Fuse, Dimensions: 5x25 mm, Trigger characteristic: Fast-acting (F); Rated voltage: 250 V, Rated current: 2 A

| Dusiness uala | |
|--|--------------------|
| Article number | 2097.0 |
| Article name | SI K 5x25 2,000A-F |
| GTIN (EAN) | 4044211049058 |
| Indicator colour | Blue |
| Packaging unit | 10 |
| Quantity unit | PC |
| Weight per piece (not including packaging) | 1.32 g |
| Weight per piece (including packaging) | 1.4 g |
| Unit of weight | G |
| Customs number | 85361010 |
| Country of origin | DE |
| Product description | fuse |

Business data



Technical data

| Dimensions | | |
|------------------------------------|----------------------|--|
| Length | 25 mm | |
| Diameter of contact cap | 5.2 mm | |
| Optical defect display available | \checkmark | |
| Dimensions | 5x25 mm | |
| Ratings | | |
| Rated voltage | 250 V | |
| Rated current | 2 A | |
| Materials | | |
| Contact caps | Brass | |
| Surface | Nickel | |
| Tube | Ceramic | |
| Further technical data | | |
| Trigger characteristic | Fast-acting (F) | |
| Rated breaking capacity | 1500 A @ AC 250 V | |
| Voltage drop | 420 mV | |
| Power loss (@ 1.5 ln) | 1.1 W | |
| Melting integral I ² ts | 2.4 A ² s | |
| Environmental Product Compliance | | |
| REACH Conform | yes | |
| REACH Reference date | 2023-06-14 | |
| REACH Candidate Substance Note | No | |
| RoHS Conform | yes | |
| | | |

Media



Accessories