



Fuse, Dimensions: 5x20 mm, Trigger characteristic: Fast-acting (F); Rated voltage: 250 V, Rated current: 6.3 A

Business data

Article number	2409.0
Article name	SI 5x20 6,300A-F
GTIN (EAN)	4044211051914
Packaging unit	10
Quantity unit	PC
Weight per piece (not including packaging)	0.84 g
Weight per piece (including packaging)	0.9 g
Unit of weight	G
Customs number	85361010
Country of origin	DE
Product description	fuse

Technical data

Dimensions

Length	20 mm
Diameter of contact cap	5.2 mm
Dimensions	5x20 mm

Ratings

Rated voltage	250 V
Rated current	6.3 A

Materials

Contact caps	Brass
Surface	Nickel
Tube	Glass

Further technical data

Trigger characteristic	Fast-acting (F)
Rated breaking capacity	63 A @ AC 250 V
Voltage drop	100 mV
Power loss (@ 1.5 I _n)	2 W
Melting integral I ² t _s	79 A ² s

Environmental Product Compliance

REACH Conform	yes
REACH Reference date	2023-06-14
REACH Candidate Substance Note	No
RoHS Conform	yes

Data sheet

2409.0 SI 5x20 6,300A-F



Approvals

Standards and regulations

Standards / specifications

IEC 60127-2/2 EN 60127-2/2 VDE 0820-2/2

Data sheet

2409.0 SI 5x20 6,300A-F



Media

Accessories
