Data sheet 2099.0 SI K 5x25 6,300A-F





Fuse, Dimensions: 5x25 mm, Trigger characteristic: Fast-acting (F); Rated voltage: 250 V, Rated current: 6.3 A

Business data

Article number	2099.0
Article name	SI K 5x25 6,300A-F
GTIN (EAN)	4044211049072
Indicator colour	Green
Packaging unit	10
Quantity unit	PC
Weight per piece (not including packaging)	1.32 g
Weight per piece (including packaging)	1.4 g
Unit of weight	G
Customs number	85361010
Country of origin	EU
Product description	fuse

Data sheet





Technical data		
Dimensions		
Length	25 mm	
Diameter of contact cap	5.2 mm	
Optical defect display available	✓	
Dimensions	5x25 mm	
Ratings		
Rated voltage	250 V	
Rated current	6.3 A	
Materials		
Contact caps	Brass	
Surface	Nickel	
Tube	Ceramic	
Further technical data		
Trigger characteristic	Fast-acting (F)	
Rated breaking capacity	1500 A @ AC 250 V	
Voltage drop	170 mV	
Power loss (@ 1.5 ln)	2.5 W	
Melting integral I2ts	63 A ² s	
Environmental Product Compliance		
REACH Conform	yes	
REACH Reference date	2023-06-14	
REACH Candidate Substance Note	No	
RoHS Conform	yes	

Data sheet 2099.0 SI K 5x25 6,300A-F



Media

Data sheet 2099.0 SI K 5x25 6,300A-F



Accessories