Data sheet 2485.1 ZB 35/K GNYE





Clamping yoke, Screw connection, Mounting type: Can be screwed on, Rated cross-section: 35 mm², Colour: Green-yellow

Business data

Article number	<u>2485.1</u>
Article name	ZB 35/K GNYE
GTIN (EAN)	4044211052775
Packaging unit	20
Quantity unit	PC
Weight per piece (not including packaging)	18.75 g
Weight per piece (including packaging)	18.76 g
Unit of weight	G
Customs number	85369010
Country of origin	DE
Prio-Article	2485.1
Product description	Clamping yoke

Data sheet





Technical data	
Dimensions	
Length	18 mm
Width	14 mm
Height	21 mm
Ratings	
Rated cross-section	35 mm²
Connection data	
Connection principle	Screw connection
Wire cross-section single-core (rigid) / stranded, min.	16 mm²
Wire cross-section single core (rigid)/stranded, max.	35 mm²
Wire cross-section stranded, min.	16 mm²
Wire cross-section stranded, max.	35 mm²
Stripping length	18 mm
Screw head	Slotted
Screw threading	M 6
Tightening torque, min.	2.5 Nm
Tightening torque, max.	5 Nm
Materials	
Material	Steel
Surface	Galvanized, thick-film passivated
Insulation housing	Polyamide 6.6
Flammability class UL 94	V-2
Working temperature, min.	-40 °C
Working temperature, max.	105 °C
Screws	Steel
Surface screw	Galvanized, thick-film passivated
Further technical data	
Mounting type	Screwable
Environmental Product Compliance	
REACH Candidate Substance Note	No

Data sheet





Media



Data sheet

2485.1 ZB 35/K GNYE



Accessories

Cap



Cap, C	Colour:	Green-y	ellow
--------	---------	---------	-------

Article number	Article name	GTIN (EAN)	Packaging unit
2490.1	K 35 GNYE	4044211052881	50

Neutral busbar



Busbar, Material: Brass, Colour: natural

Article number	Article name	GTIN (EAN)	Packaging unit
2128.0	Ssch 10x3 MS	4044211049478	1 M



Busbar, Material: Copper, Colour: natural

Article number	Article name	GTIN (EAN)	Packaging unit
2129.0	Ssch 10x3 CU	4044211049485	1 M