

Disconnect-blade terminal, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Beige

Business data

| | |
|--|---------------------------|
| Article number | <u>3605.2</u> |
| Article name | ZTRK 2,5/4A/MT BG |
| GTIN (EAN) | 4044211059699 |
| Packaging unit | 100 |
| Quantity unit | PC |
| Weight per piece (not including packaging) | 12.6 g |
| Weight per piece (including packaging) | 13.46 g |
| Unit of weight | G |
| Customs number | 85369010 |
| Country of origin | CZ |
| Prio-Article | 3605.2 |
| Product description | Disconnect-blade terminal |

Technical data

Dimensions

| | |
|------------------|---------|
| Length | 92.4 mm |
| Width | 5.1 mm |
| Height TS 35/7.5 | 42.3 mm |

Ratings

| | |
|---|---------------------|
| Rated voltage | 400 V |
| Rated current | 18 A |
| Rated cross-section | 2.5 mm ² |
| Rated impulse voltage | 6 kV |
| Overvoltage category | III |
| Contamination degree | 3 |
| Maximum power dissipation for nominal condition | 0.58 W |

Connection data

| | |
|--|---------------------------|
| Connection principle | Tension-spring connection |
| Connection position | Diagonal |
| Connections | 4 |
| Number of terminals per level | 4 |
| Number of levels | 1 |
| Wire cross-section single-core (rigid) / stranded, min. | 0.5 mm ² |
| Wire cross-section single core (rigid)/stranded, max. | 4 mm ² |
| Wire cross-section stranded, min. | 0.5 mm ² |
| Wire cross-section stranded, max. | 4 mm ² |
| Wire cross-section stranded with wire-end ferrules, min. | 0.5 mm ² |
| Wire cross-section stranded with wire-end ferrules, max. | 2.5 mm ² |
| Wire cross-section AWG, min. | 20 |
| Wire cross-section AWG, max. | 12 |
| Stripping length | 10 mm |

Materials

| | |
|---------------------------|---------------|
| Insulation housing | Polyamide 6.6 |
| Flammability class UL 94 | V-0 |
| Working temperature, min. | -40 °C |
| Working temperature, max. | 120 °C |

Technical data

Further technical data

| | |
|-------------------------------------|-------------------------|
| Mounting type | Mounting rail TS 35/7,5 |
| Gauge plug acc. to EN 60 947-1 | A3 |
| Number of cross-connection channels | 1 |
| End plate required | ✓ |
| Number of test pick-off options | 2 |
| Version of lengthwise partition | Swivelling |

Environmental Product Compliance

| | |
|--------------------------------|----|
| REACH Candidate Substance Note | No |
|--------------------------------|----|

Approvals

CSA approval

| | |
|--------------------------------------|--------------|
| CSA approval | C22.2 No 158 |
| CSA approval granted | yes |
| CSA Usegroup B: rated current (fuse) | 15 A |
| CSA Usegroup C: rated voltage (fuse) | 300 V |
| CSA Usegroup B: rated voltage (fuse) | 300 V |
| CSA Usegroup C: rated current (fuse) | 15 A |
| CSA wire cross-section AWG, min. | 20 |
| CSA wire cross-section AWG, max. | 12 |
| CSA stripping length | 10 mm |


CSAus approval

| | |
|--|---------|
| CSAus approval | UL 1059 |
| CSAus approval granted | yes |
| CSAus Usegroup B: rated voltage (fuse) | 300 V |
| CSAus Usegroup B: rated current (fuse) | 15 A |
| CSAus Usegroup C: rated voltage (fuse) | 300 V |
| CSAus Usegroup C: rated current (fuse) | 15 A |
| CSAus wire cross-section AWG, min. | 20 |
| CSAus wire cross-section AWG, max. | 12 |
| CSAus stripping length | 10 mm |

KEMA KEUR approval

| | |
|--|--------------------------------------|
| KEMA KEUR approval | EN 60947-7-1:2009, EN 60947-7-3:2009 |
| KEMA KEUR approval granted | yes |
| KEMA rated voltage (fuse) | 400 V |
| KEMA rated current (diode) | 18 (1) A |
| KEMA rated impulse voltage (fuse holder without electrical components) | 6 kV |
| KEMA wire cross-section single core (rigid), min. | 0.5 mm ² |
| KEMA wire cross-section single-core (rigid), max. | 4 mm ² |
| KEMA wire cross-section stranded, min. | 0.5 mm ² |
| KEMA wire cross-section stranded, max. | 4 mm ² |

Media



Accessories

End plate

End plate, Width: 1.5 mm, Colour: Beige



| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|----------------|---------------|----------------|
| <u>3798.2</u> | ZAPT 2,5/4A BG | 4044211061326 | 20 |

Actuating tool


Actuating tool, No. of poles: 1, Colour: Black



| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|-----------------------|---------------|----------------|
| <u>3808.0</u> | BWMA 1 (0,5 x 3,5 mm) | 4044211078850 | 1 ST |

End stop

End stop, Mounting type: Mounting rail TS 35/7.5 and TS 35/15, Width: 6 mm, Colour: Beige



| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|--------------|---------------|----------------|
| <u>3748.2</u> | ZES 35 BG | 4044211060572 | 50 |

Test adapter

Test adapter, Pitch size: 5.1 mm, Colour: Beige



| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|--------------|---------------|----------------|
| <u>3740.2</u> | ZTA 2,5 BG | 4044211060497 | 10 ST |

Insulated cross-connector

3605.2 ZTRK 2,5/4A/MT BG



Insulated cross-connector, No. of poles: 7, Mounting type: Plug in, Width: 34.6 mm, Rated cross-section: 2.5 mm², Colour: Yellow

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|--------------|---------------|----------------|
| <u>3715.8</u> | ZQI 2,5/7 YE | 4044211060336 | 20 |



Insulated cross-connector, No. of poles: 2, Mounting type: Plug in, Width: 9.1 mm, Rated cross-section: 2.5 mm², Colour: Yellow

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|--------------|---------------|----------------|
| <u>3710.8</u> | ZQI 2,5/2 YE | 4044211060282 | 50 |



Insulated cross-connector, No. of poles: 10, Mounting type: Plug in, Width: 49.9 mm, Rated cross-section: 2.5 mm², Colour: Yellow

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|---------------|---------------|----------------|
| <u>3718.8</u> | ZQI 2,5/10 YE | 4044211060367 | 10 |



Insulated cross-connector, No. of poles: 3, Mounting type: Plug in, Width: 14.2 mm, Rated cross-section: 2.5 mm², Colour: Yellow

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|--------------|---------------|----------------|
| <u>3711.8</u> | ZQI 2,5/3 YE | 4044211060299 | 50 |



Insulated cross-connector, No. of poles: 5, Mounting type: Plug in, Width: 24.4 mm, Rated cross-section: 2.5 mm², Colour: Yellow

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|--------------|---------------|----------------|
| <u>3713.8</u> | ZQI 2,5/5 YE | 4044211060312 | 20 |



Insulated cross-connector, No. of poles: 8, Mounting type: Plug in, Width: 39.7 mm, Rated cross-section: 2.5 mm², Colour: Yellow

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|--------------|---------------|----------------|
| <u>3716.8</u> | ZQI 2,5/8 YE | 4044211060343 | 10 |

3605.2 ZTRK 2,5/4/MT BG



Insulated cross-connector, No. of poles: 4, Mounting type: Plug in, Width: 19.3 mm, Rated cross-section: 2.5 mm², Colour: Yellow

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|--------------|---------------|----------------|
| <u>3712.8</u> | ZQI 2,5/4 YE | 4044211060305 | 20 |



Insulated cross-connector, No. of poles: 6, Mounting type: Plug in, Width: 29.5 mm, Rated cross-section: 2.5 mm², Colour: Yellow

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|--------------|---------------|----------------|
| <u>3714.8</u> | ZQI 2,5/6 YE | 4044211060329 | 20 |

Insulated cross-connector, No. of poles: 99, Mounting type: Plug in, Width: 500 mm, Rated cross-section: 2.5 mm², Colour: Yellow

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|--------------------------|---------------|----------------|
| <u>3719.8</u> | ZQI 2,5/0,5 m/99 Pole YE | 4044211060374 | 2 |

Quick marking



Terminal marker / Pocket Maxicard, Length: 5 mm, Width: 5 mm, Colour: White

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|----------------|---------------|----------------|
| <u>4600.7</u> | PMC SB 5/50 WH | 4044211088903 | 500 ST |

Four-way cover



Cover, Length: 6.7 mm, Width: 20.4 mm, Colour: Yellow

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|----------------|---------------|----------------|
| <u>3706.0</u> | ZAD 2,5/4/B YE | 4044211060244 | 20 ST |

Reducing sleeves

3605.2 ZTRK 2,5/4A/MT BG

Reducing sleeve, Width: 51 mm, Pitch size: 5.1 mm, Colour: Grey



| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|---------------------|---------------|----------------|
| <u>3751.6</u> | ZRH 2,5/0,25-0,5 GR | 4044211060602 | 1000 ST |

Reducing sleeve, Width: 51 mm, Pitch size: 5.1 mm, Colour: White



| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|---------------------|---------------|----------------|
| <u>3750.7</u> | ZRH 2,5/0,13-0,2 WH | 4044211060596 | 1000 ST |

Reducing sleeve, Width: 51 mm, Pitch size: 5.1 mm, Colour: Black



| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|---------------------|---------------|----------------|
| <u>3752.4</u> | ZRH 2,5/0,75-1,0 BK | 4044211060619 | 1000 ST |